

型号 (type)		HM5545THB-75 HM5546THB-75
整车参数 (Vehicle)	全长 (Full length)	16720mm
	总宽 (Total width)	2550mm
	总高 (Total height)	4000mm
	自重 (Self weight)	54000kg
臂架支腿参数 (Boom&Outrigger)	臂架垂直高度 (Boom vertical height)	74.5m
	臂架水平长度 (Boom horizontal length)	68.9m
	臂架垂直深度 (Boom vertical depth)	56.1m
	最小展开高度 (Minimum expansion height)	16.8m
	第一节臂 (First arm)	长度 (Length) 13935mm 转角 (Corner) 90°
	第二节臂 (Second arm)	长度 (Length) 10615mm 转角 (Corner) 180°
	第三节臂 (Third arm)	长度 (Length) 10225mm 转角 (Corner) 180°
	第四节臂 (Fourth arm)	长度 (Length) 13250mm 转角 (Corner) 230°
	第五节臂 (Fifth arm)	长度 (Length) 13800mm 转角 (Corner) 180°
	第六节臂 (Sixth arm)	长度 (Length) 8620mm 转角 (Corner) 200°
	转台旋转角度 (Turntable rotation angle)	±270°
	前支腿展开宽度 (Front leg deployment width)	12745mm
	后支腿展开宽度 (Rear leg deployment width)	15800mm
泵送系统参数 (Pumping system)	混凝土排量 (Concrete displacement)	180m³/h
	理论泵送压力 (Pressure) 高压/低压	12/8.2Mpa
	理论泵送次数 (Theoretical pumping times)	28次/分钟
	输送缸内径 (Delivery cylinder inner diameter)	260mm
	输送缸行程 (Delivery cylinder stroke)	2200mm
	液压系统 (Hydraulic system)	开式液控
	系统油压 (System oil pressure)	32Mpa
	油箱体积 (Tank volume)	600L
	水箱容积 (Water tank volume)	400L
	输送管径 (Conveying pipe diameter)	125mm
	末端软管长度 (End hose length)	3m
底盘参数 (Chassis)	底盘型号 (Chassis model)	五桥陕汽 SX5449XDCZ2 五桥豪沃 ZZ5547V42KGF1
	发动机型号 (engine model)	WP13.510E62 MC13.54-61
	发动机功率 (Engine power)	375/400KW
	排放标准 (Emission Standards)	国 VI
	排量 (Displacement)	12.5/12.419L

